

EX GRIP PRO TRACTION PRO TRAC ENDURANCE

PRO



EX GRIP PRO
E3



EX TRACTION PRO
E3



EX TRACTION PRO*
E3



EX TRAC
E4



EX ENDURANCE PRO
E4



EX GRIP
E4

SPECIAL DESIGN FOR WIDEBODY DUMPER TRUCK

- ❑ EXTRA Traction in all off-road conditions
- ❑ EXTRA Reinforced all-steel radial casing provides superior loading performance
- ❑ EXTRA Wear and cut-resistant tread compound
- ❑ EXTRA Wide, flat footprint profile for maximum stability and wear rate
- ❑ EXTRA Deep under-tread for improved puncture resistance



Size	Pattern	TRA	TT/TL	Tread Depth (mm)	Rim	Star Rating	Overall Diameter (mm)	Section Width (mm)	Loading Capacity		Inflation (KPa)	
									10km/h	50km/h	10km/h	50km/h
14.00R25	EX GRIP PRO	E3	TT	28.5	10.00/2.0	☆☆☆	1370	375	10000	5800	1000	800
16.00R25	EX GRIP PRO	E3	TT/TL	32.5	11.25/2.0	☆☆☆	1495	430	12850	7300	1000	900
14.00R25	EX TRACTION PRO	E3	TT	27	10.00/2.0	☆☆☆	1370	375	10000	5800	1000	800
16.00R25	EX TRACTION PRO	E3	TT/TL	32	11.25/2.0	☆☆☆	1495	430	12850	7300	1000	900
16.00R25	EX TRACTION PRO*	E3	TT/TL	29	11.25/2.0	☆☆☆	1518	430	12850	7300	1000	900
480/95R29	EX TRACTION PRO	E3	TT	31	13.00/2.5	☆☆☆	1627	480	16000		1000	
14.00R25	EX TRAC	E4	TT	40	10.00/2.0	☆☆☆	1368	375	10000	5800	1000	800
16.00R25	EX TRAC	E4	TT/TL	43	11.25/2.0	☆☆☆	1548	432	12500	8500	1000	900
14.00R25	EX ENDURANCE PRO	E4	TT	40	10.00/2.0	☆☆☆	1370	375	10000	5800	1000	800
16.00R25	EX ENDURANCE PRO	E4	TT/TL	39.5	11.25/2.0	☆☆☆	1495	430	12850	7300	1000	900
14.00R25	EX GRIP	E4	TT	36	10.00/2.0	☆☆☆	1368	375	10000	6050	1000	800
16.00R25	EX GRIP	E4	TT/TL	46	11.25/2.0	☆☆☆	1548	448	12500	8500	1000	900

EX GRIP TRACTION TRAC ENDURANCE PRO

SPECIAL DESIGN FOR WIDEBODY DUMPER TRUCK



COMPOUND
STANDARD
STANDARD & CUT RESISTANT
CUT RESISTANT
SUPER CUT RESISTANT
HEAT RESISTANT

